

## SA Rod end PM17-01-501-DURBAL - PM17-01-501-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/sa/pm17-01-501-durbal>

### PM17-01-501



**male thread:**  
long-term lubrication, low maintenance, shields

**DURBAL® heavy-duty rod ends with integral self-aligning ball bearing**

**rod end housing:**  
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

**inner ring:**  
ball bearing steel, hardened, superfinished

**lubrication:**  
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to ISO/A H1

**lubrication fitting:**  
DIN 3405 D1/A

**bearing clearance:**  
10 - 30 µm radial

**tolerances:**  
see page 10

order number		measurements [mm]		measurements [mm]		weight		rotational speed limit		basic load rating		
type	type	d1	d2	d4	d7	b1	b2	Y	Yc	C	C0	
PM 17 -01	-501	17	M 20 x 1,5	21,0	48	22	16					
measurements [mm]		weight		rotational speed limit		basic load rating						
type	l1	l2	l3	h1	h2	u	z	alpha	alpha prime	Y	Yc	
PM 17	36	36	78,5	3,5	2,5	7,0	0,354	2,35	2,46	875	5575	2680

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952507699
Inside diameter	17 mm
Outside diameter	48 mm
Thickness	22 mm
Type	SA
Weight	354 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE