

SA Rod end PM20-00-501-DURBAL - PM20-00-501-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/sa/pm20-00-501-durbal>

PM20-00-501



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]			measurements [mm]			measurements [mm]		
type	sp. hand thread	id. bore dia.	d ₁	d ₂	d ₄	d ₅	d ₇	b ₁	b ₂	b ₃
PM 20 -00	-501	20	M 24 x 1.5	24.0	56	30	24	18		

type	measurements [mm]						weight [kg]	calculation factors		rotational speed limit [min ⁻¹]	basic load rating	
	l ₁	l ₂	l ₃	h ₁	h ₂	u		Y	Y ₀		C [N]	C ₀ [N]
PM 20	68,5	41	117	3,5	3,0	5,5	0,587	2,76	2,90	775	6165	3140

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952507705
Inside diameter	20 mm
Outside diameter	56 mm
Thickness	24 mm
Type	SA
Weight	587 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE