

SI Rod end BRF16-60-501-DURBAL - BRF16-60-501-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/si/brf16-60-501-durbal>

BRF16-60-501

rod end housing:
stainless steel 1.4534, hardened, bearing race superfinished

inner ring:
stainless steel, hardened, surface superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3405 D1/A (sizes 6 to 10)
DIN 71 412 H1 (sizes 12 to 20)

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing in stainless steel

female thread;
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K

order number		measurements [mm]											
type	right-hand thread	d ₁	d ₂	d ₃	d ₄	d ₅	d ₆	d ₇	b ₁	b ₂	h		
BRF 16 -60 -501		16	22,0	M 16	19,0	42	27	21	15,0	64			
measurements [mm]		weight		calculation-factors		rotational speed limit		basic load rating		stat.			
type	l	l ₁	l ₂	SW	α [°]	Y	λ	n _{max} [min ⁻¹]	C	C ₀	C ₁₀	C ₅₀	
BRF 16	28	8,0	22	22	8,0	0,224	2,24	2,35	975	4250	1600		

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952509280
Inside diameter	16 mm
Outside diameter	42 mm
Thickness	21 mm
Type	SI
Weight	224 g
Thread	Right-hand thread
Lubrication	with
Packaging	1
Standard	No standard

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE