

SA Rod end BRM3-4-00-501-DURBAL - BRM3-4-00-501-DURBAL

<https://www.123bearing.eu/bearing-housing/rod-end/sa/brm3-4-00-501-durbal>

BRM3/4-00-501



male thread:
long-term lubrication, low maintenance, shields, dimensions in inches

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminum-complex soap grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3425 D11A (sizes 1/4 and 3/8)
DIN 71 412 H1 (sizes 1/2 and 1/1)

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [inches]							
type	right hand thread, left hand thread	d ₁	d ₂ class 2	d ₃	d ₄	d ₅	b ₁	b ₂	b ₃
BRM3/4-00	-501	.750	.7500-16 UNF	.956	1.968	.984	.708		
measurements [inches]		weight		calculation factors		rotational speed limit		basic load rating stat.	
type	h	l	l ₃	α [°]	Y	v ₀	f _{max} [min ⁻¹]	C [N]	C ₀ [N]
BRM3/4	3.090	1.850	1.102	7,0	0,341	2,32	2,43	825	7750 3380

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952510323
Inside diameter	19.05 mm
Outside diameter	49.99 mm
Thickness	24.99 mm
Type	SA
Weight	341 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE