


Other bearings ARNB2062-NADELLA - ARNB2062-NADELLA

<https://www.123bearing.eu/bearing-housing/other-bearings/arnb2062-nadella>

**Precision combined bearings,
with adjustable axial preload**



AXNB and ARNB series



| Shaft d mm | Designation | | | | d mm | D mm | F _w mm | D _a mm | D _m mm | B mm | C mm | B ₁ mm | r mm | f ₁ mm |
|------------------|-------------|------------------|------------------|------------------|---------|---------|----------------------|----------------------|----------------------|---------|---------|----------------------|---------|----------------------|
| | AXNB | ARNB series 1 | ARNB series 2 | ARNB series 3 | | | | | | | | | | |
| 20 | | | | 20 62 | 20 | 62 | 30 | 52 | 39.9 | 60 | 20 | 20 | 1.3 | 0.85 |

| Load Ratings kN | | | | Speed rating min ⁻¹ | Preload ¹⁾ N | Rotation ²⁾ torque Nmm | Rigidity K ³⁾ N/mm | Weight kg | Designation |
|-----------------|----------|--------|----------|--------------------------------------|----------------------------|---|----------------------------------|--------------|-------------|
| radial | | axial | | | | | | | |
| Dyn. C | Stat. Co | Dyn. C | Stat. Co | | | | | | |
| 28.0 | 44.5 | 48.0 | 115.0 | 6300 | 3010 | 1200 | 1130 | 0.875 | ARNB 20 62 |

1) 6% of dynamic axial load - 2) with axial load equal to preload - 3) rigidity of a single thrust bearing with load equal to preload

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | NADELLA |
| N° Ean13 | 3663952530321 |
| Inside diameter | 20 mm |
| Outside diameter | 52 mm |
| Thickness | 60 mm |
| Weight | 875 g |
| Packaging | 1 |

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE