




Drawn cup roller bearing TJ7214-RBC - TJ7214-RBC

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/drawn-cup/tj7214-rbc>

Heavy Duty TJ TandemRoller® Bearings 

TJ TandemRoller® Bearing

BEARING PART NUMBER 1)	Fw Inside Diameter			D Outside Diameter		B Width	r _s Housing Fillet	Housing Shoulder Dia	Dynamic Capacity C (lbs.)	Static Capacity C ₀ (lbs.)
	Nominal	Min.	Max.	Max.	Min.	+0.00 -0.00	Max	±.184"		
TJ 7214	1.18	1.1259	1.1268	1.3250	1.3240	1.000	.040	1.38	8,500	15,500

Limit Speed (rpm)	Recommended Shaft Diameter				Recommended Housing Bore				BEARING PART NUMBER 1)		
	ISO N6 use with H7 fit	ISO R6 use with H7 fit	ISO R6 use with H7 fit	ISO R6 use with H7 fit	Slip Fit ISO H7	Press Fit ISO N7	Press Fit ISO N7	Press Fit ISO N7			
	Max.	Min.	Max.	Min.	Min.	Max.	Mean Ft	Min.	Max.	Mean Ft	
10,500	1.1290	1.1245	1.1242	1.1237	1.6250	1.6280	.0007L	1.6237	1.6247	.0006T	TJ 7214

All dimensions in inches.
1) Prefix DTJ denotes a double row bearing.

PRODUCT FEATURES

Brand	RBC
N° Ean13	3663952533490
Inside diameter	28.575 mm
Inside diameter	1 1/8" inch
Outside diameter	41.275 mm
Outside diameter	1 5/8" inch
Thickness	25.4 mm
Thickness	1" inch
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE