




Drawn cup roller bearing DTJ75168-RBC - DTJ75168-RBC

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/drawn-cup/dtj75168-rbc>

Heavy Duty TJ TandemRoller® Bearings 

DTJ Double Row TandemRoller® Bearing

BEARING PART NUMBER 1)	Fw Inside Diameter			D Outside Diameter		B Width +0.00 -0.00	r _s Housing Fillet Max	Housing Shoulder Dia ±0.184*	Dynamic Capacity C (lbs.)	Static Capacity C ₀ (lbs.)
	Nominal	Min.	Max.	Max.	Min.					
DTJ 75168	3 1/4	3.2512	3.2524	4.2505	4.2492	4.000	.060	3.314	54,500	184,500

BEARING PART NUMBER 1)	Recommended Shaft Diameter						Recommended Housing Bore				
	Limit Speed (rpm)	ISO H6 use with H7 fit 1)		ISO H6 use with N7 fit 1)		Min.	Slip Fit ISO H7		Press Fit ISO N7		
		Max.	Min.	Max.	Min.		Max.	Mean Fit	Min.	Max.	Mean Fit
DTJ 75168	3,300	3.2500	3.2491	3.2466	3.2477	4.2500	4.2514	.0011L	4.2482	4.2496	.0007T

All dimensions in inches.
1) Prefix DTJ denotes a double row bearing.

PRODUCT FEATURES

Brand	RBC
N° Ean13	3663952533650
Inside diameter	82.55 mm
Outside diameter	107.95 mm
Thickness	101.6 mm
Packaging	1
Standard	No standard

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE