




Drawn cup roller bearing TJ75176-RBC - TJ75176-RBC

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/drawn-cup/tj75176-rbc>

Heavy Duty TJ TandemRoller® Bearings 

TJ TandemRoller® Bearing

BEARING PART NUMBER	Fw Inside Diameter			D Outside Diameter		B Width	r _s Housing Fillet	Housing Shoulder Dia	Dynamic Capacity C (lbs.)	Static Capacity C ₀ (lbs.)
	Nominal	Min.	Max.	Min.	Max.	+0.00 -0.00	Max	±0.004"		
TJ 75176	4.176	4.0643	4.0607	4.6250	4.6242	1.500	.000	4.576	18,900	81,000

Limit Speed (rpm)	Recommended Shaft Diameter					Recommended Housing Bore					BEARING PART NUMBER
	ISO H6 use with H7 fit		ISO H6 use with N7 fit			Slip Fit ISO H7			Press Fit ISO N7		
	Max.	Min.	Max.	Min.	Min.	Max.	Mean Fit	Min.	Max.	Mean Fit	
2,800	4.0625	4.0616	4.0611	4.0602	4.6250	4.6256	.0015	4.6250	4.6245	.0007	TJ 75176

All dimensions in inches.
1) Prefix DTJ denotes a double row bearing.

PRODUCT FEATURES

Brand	RBC
N° Ean13	3663952533711
Inside diameter	103.188 mm
Outside diameter	117.475 mm
Thickness	38.1 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE