




Drawn cup roller bearing TJ6849-RBC - TJ6849-RBC

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/drawn-cup/tj6849-rbc>

Heavy Duty TJ TandemRoller® Bearings 

TJ TandemRoller® Bearing

BEARING PART NUMBER 1)	Fw Inside Diameter			D Outside Diameter		B Width	r _s Housing Fillet	Housing Shoulder Dia	Dynamic Capacity C (lbs.)	Static Capacity C ₀ (lbs.)
	Nominal	Min.	Max.	Max.	Min.	+0.000 -0.005	Max	±0.184"		
TJ 6849	5	5.0013	5.0027	6.5000	6.4990	2.250	.100	5.314	54,000	137,000

Limit Speed (rpm)	Recommended Shaft Diameter				Recommended Housing Bore				BEARING PART NUMBER 1)		
	ISO N6 use with H7 fit	ISO R6 use with N7 fit	ISO R6 use with N7 fit	ISO R6 use with N7 fit	Slip Fit ISO H7	Press Fit ISO N7	Press Fit ISO N7	Press Fit ISO N7			
2,400	5.0000	4.9990	4.9983	4.9973	6.5000	6.5016	.0013	6.4990	6.4995	.0008	TJ 6849

All dimensions in inches.
1) Prefix DTJ denotes a double row bearing.

PRODUCT FEATURES

Brand	RBC
N° Ean13	3663952533773
Inside diameter	127 mm
Inside diameter	5" inch
Outside diameter	165.1 mm
Outside diameter	6 1/2" inch
Thickness	57.15 mm
Thickness	2 1/4" inch
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE