

## Deep groove ball bearing single row 1614-NS-NICE - 1614-NS-NICE

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/single-row/1614-ns-nice>

**1600** Series™ Precision Ground Radial Bearings **NICE**



SUFFIX					PRINCIPLE DIMENSIONS		
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
	+0.000	+0.000	-0.005	-0.013		0.3750 9.525	1.250 28.575
1614™					NS		
BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS			
WIDTH B (in) (mm)	DYNAMIC C (lb) (N)	STATIC C <sub>0</sub> (lb) (N)	W <sup>0</sup> (lb) (g)	d <sub>a</sub> min (in) (mm)	D <sub>a</sub> max (in) (mm)	r max (in) (mm)	
0.3750 9.525	1200 5340	475 2114	0.06 0.03	0.595 15.11	1.014 25.76	0.025 0.64	

Weights given are for greased and sealed versions

### PRODUCT FEATURES

Brand	NICE
N° Ean13	3663952557243
Inside diameter	9.525 mm
Outside diameter	28.575 mm
Thickness	9.525 mm
Weight	30 g
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE