


## Deep groove ball bearing single row 1623-SC-NICE - 1623-SC-NICE

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/single-row/1623-sc-nice>

**1600** Series™ Precision Ground Radial Bearings (con't) **NICE**



SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
						+0.000 +0.000 -0.0005 -0.013	+0.000 +0.000 -0.0005 -0.013
1623™		SC				0.6250 15.875	1.2750 34.925
BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS			
WIDTH B (in) (mm)	DYNAMIC C (lb) (N)	STATIC C <sub>0</sub> (lb) (N)	W <sup>0</sup> (kg)	d <sub>a</sub> min (in) (mm)	D <sub>a</sub> max (in) (mm)	r max (in) (mm)	
0.4375 11.113	1878 8367	850 3783	0.10 0.05	0.753 19.13	1.203 30.56	0.025 0.64	

Weights given are for greased and sealed versions

### PRODUCT FEATURES

Brand	NICE
N° Ean13	3663952557489
Inside diameter	15.875 mm
Inside diameter	5/8" inch
Outside diameter	34.925 mm
Outside diameter	1 3/8" inch
Thickness	11.113 mm
Thickness	7/16" inch
Weight	50 g
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE