


Deep groove ball bearing single row 3002-NS-NICE - 3002-NS-NICE

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/single-row/3002-ns-nice>

3000 Series® Semi-Ground Radial Bearings **NICE**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES™ BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- INFLUX RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE



SUFFIX					PRINCIPLE DIMENSIONS		
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
						+0.005 +0.13 -0.000 -0.00	+0.000 +0.00 -0.0005 -0.013
3002™					NS	0.2500 6.350	0.5675 17.463

BASIC LOAD RATINGS		WEIGHT		ABUTMENT AND FILLET DIMENSIONS		
WIDTH B (in) (mm)	DYNAMIC C (lbs) (N)	STATIC Co (lbs) (N)	W (lb) (kg)	da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)
0.2500 6.350	255 1135	170 757	0.02 0.01	0.330 8.38	0.614 15.60	0.012 0.30

Width for sealed versions = 0.3125 (7.938) Weights given are for greased and sealed versions
3008 and larger +0.0005/-0.005 (-0.001/-0.15)

PRODUCT FEATURES

Brand	NICE
N° Ean13	3663952558042
Inside diameter	6.35 mm
Outside diameter	17.463 mm
Thickness	6.35 mm
Weight	10 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE