Deep groove ball bearing single row
3004-DS-NICE - 3004-DS-NICE

https://www.123bearing.eu/bearing-housing/deep-groove-bearing/single-row/3004-ds-nice



3000 Series® Semi-Ground Radial Bearings

NICE

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1600 SERIES™ BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- NYLON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm) +.005 +0.13 -.000 -.00	O.D. D (in) (mm) +.0000 +.00 -.0005 -0.013
3004™			DS			0.3750 9.525	0.8750 22.225

BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
WIDTH B (in) (mm) +.005 +.00 -.005 -.13	DYNAMIC C (lbs) (N)	STATIC Co (lbs) (N)	W (lbs) (kg)	d_a min (in) (mm)	D_a max (in) (mm)	r max (in) (mm)
0.2813 7.1450	325 1448	255 1135	0.03 0.01	0.474 12.04	0.778 19.76	0.015 0.38

Width for sealed versions = 0.3438 (8.733)

Weights given are for greased and sealed versions

3038 and larger +.0000/-.0006 (+.000/-.015)

PRODUCT FEATURES

Brand	NICE
N° Ean13	3663952558127
Inside diameter	9.525 mm
Outside diameter	22.225 mm
Thickness	7.145 mm
Weight	10 g
Packaging	1

contact@123bearing.eu
+33 359 36 04 90
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE