

## Deep groove ball bearing single row 3028-SS-NICE - 3028-SS-NICE

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/single-row/3028-ss-nice>

**3000 Series® Semi-Ground Radial Bearings (con't)** **NICE**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES™ BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- INFLUX RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3028™				SS		+0.005 +0.13 -0.000 -0.00	+0.000 +0.00 -0.0005 ⓪
						0.6250 15.875	1.5250 41.275

BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
WIDTH B (in) (mm)	DYNAMIC C (lb) (N)	STATIC Co (lb) (N)	W <sup>⓪</sup> (lb) (kg)	da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)
0.5000 12.700	1300 5795	1010 4489	0.18 0.08	0.845 21.46	1.446 36.73	0.025 0.64

<sup>⓪</sup> Weights given are for greased and sealed versions  
<sup>⓪</sup> 3028 and larger +0.0005/-0.005 (+0.002/-0.15)

### PRODUCT FEATURES

Brand	NICE
N° Ean13	3663952558615
Inside diameter	15.875 mm
Outside diameter	41.275 mm
Thickness	12.7 mm
Weight	80 g
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE