


Deep groove ball bearing single row 410-30V-NICE - 410-30V-NICE

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/single-row/410-30v-nice>

400 Series® Single Row Unground Radial Bearings **NICE®**

- RADIAL UNGROUND BEARING
- EASY TO USE INCH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- BEARING SUPPLIED PRE-GREASED STANDARD



BEARING	SUFFIX	BEARING DIMENSIONAL DATA				BALLS	
		A BORE (in) (mm)	B O.D. (in) (mm)	C WIDTH (in) (mm)	D WIDTH (in) (mm)	No.	Size
410™	30V	0.625 15.88 +0.0002 -0.0004	3.375 84.93 +0.0050 -0.0000	0.470 11.94 +0.0100 -0.0100	0.500 12.70 Reference	16	3/16 4.75

WEIGHT W (lbs) (kg)	RADIAL CAPACITY					
	REVOLUTIONS PER MINUTE					
	50	100	200	300	600	1200
0.10	375	261	180	145	101	71
0.05	1989	1181	821	645	449	316

Notes
Balls - Carbon Steel Grade 200 Bands - 1010 Carbon Steel, Soft
Rings - Carbon Steel, Case Hardened Bearings supplied prelubricated with grease

PRODUCT FEATURES

Brand	NICE
N° Ean13	3663952560113
Inside diameter	15.88 mm
Outside diameter	34.93 mm
Thickness	11.94 mm
2nd Thickness	12.7 mm
Weight	50 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE