

## Deep groove ball bearing single row 602-V-NICE - 602-V-NICE

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/single-row/602-v-nice>

**600 Series™ Unground Thrust Bearings** **NICE**

- UNGROUND THRUST BEARING
- EASY TO USE INCH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1300 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- TOP STEEL BAND OFFERS EASE OF INSTALLATION
- LOWER RING IS FREE TO ROTATE AND HAS CLEARANCE FIT FOR SHAFTS
- LOWER RING IS FIRED AND HAS SHAFT CLEARANCE IN THE BORE

BEARING DIMENSIONAL DATA							
BEARING	SUFFIX	A	A1	B	C	BALLS	WEIGHT
		BORE (in) (mm)	BORE (in) (mm)	O.D. (in) (mm)	HEIGHT (in) (mm)		
602™	V	.375 9.53	+.010 +.254	1.384 35.14	.359 9.12	14 5/22 3.97	0.06 1.65 0.03

THRUST CAPACITY						
REVOLUTIONS PER MINUTE						
10	50	100	250	500	1000	
(lbs)	(lbs)	(lbs)	(lbs)	(lbs)	(lbs)	(N)
426	344	254	138	100	71	
1896	1531	1130	614	445	318	

**Notes**  
 Balls - Carbon Steel Grade 52100  
 Washers - Carbon Steel Case Hard  
 Bands - Carbon Steel Soft  
 Bearings Oiled with a Rust Preventative  
 All Bearings Marked on Band with "Designation Nice USA" as Shown

## PRODUCT FEATURES

Brand	NICE
N° Ean13	3663952560342
Inside diameter	9.53 mm
Inside diameter	3/8" inch
Outside diameter	26.59 mm
Outside diameter	1.047" inch
Thickness	9.12 mm
Thickness	0.359" inch
Weight	30 g
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE