

Housed bearing 2 bolts N6906-B-NICE - N6906-B-NICE

<https://www.123bearing.eu/bearing-housing/housed-bearing/cast-iron-housed-bearing-2/n6906-b-nice>

6900 Series™ Semi-Ground Radial Bearings, Extended Inner with Flanged Housing **NICE**

- EASY TO USE WITH DIMENSIONS
- MEDIUM LOADS
- MAX SPEED RANGE : 3000 - 3000 RPM
- THROUGH HARDNESS
- RETAINER DESIGN
- NYLON RETAINER STANDARD
- SHOULDER BEADED STANDARD
- EXTENDED INNER RING WITH TWO SET SCREWS
- BEARINGS ARE AVAILABLE WITH OR WITHOUT FLANGE

When Ordering specify whether assembly of bearing only is required.
Bearings are stamped with designation and a "B" for example 6906-B. Housing's no longer carry the numbers.
Tolerance for 6912 and larger is ± 0.005 - -0.005 (-015)

BEARING		PRINCIPLE DIMENSIONS					
FLANGED UNIT	BEARING ONLY	Bore d (in) (mm)	O.D. D (in) (mm)	Width B (in) (mm)	Width E (in) (mm)	E (in) (mm)	F (in) (mm)
	SUFFIX	+0.005 -0.010	+0.000 +0.000	+0.000 +0.000	-0.005 -0.005		
N6906™	B	0.375 9.53	0.9063 23.020	0.313 7.94	0.688 17.46	0.555 14.10	0.375 9.53

PRODUCT FEATURES

Brand	NICE
N° Ean13	3616060473349
Shaft diameter	9.53 mm
No. of fasteners	2
Tightening	set screw
Mounting center distance	47.63 mm
Material	TOLE
Weight	30 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE