

Housed bearing 2 bolts N6910-B-NICE - N6910-B-NICE

<https://www.123bearing.eu/bearing-housing/housed-bearing/cast-iron-housed-bearing-2/n6910-b-nice>

6900 Series™ Semi-Ground Radial Bearings, Extended Inner with Flanged Housing **NICE**

- EASY TO USE INCH DIMENSIONS
- MEDIUM LOADS
- MAX SPEED RANGE: 3000 - 3000 RPM
- THROUGH HARDNESS
- RETAINER DESIGN
- NYLON RETAINER STANDARD
- SHOULDER BEADED STANDARD
- EXTENDED INNER RING WITH TWO SET SCREWS
- BEARINGS ARE AVAILABLE WITH OR WITHOUT FLANGES

When Ordering specify whether assembly of bearing only is required.
Bearings are stamped with designation and a "B" for example 6904™B. Housing's no longer carry numbers.
Tolerance for 6912 and larger is ± 0.020 (-0.001-0.015)

BEARING		PRINCIPLE DIMENSIONS					
		Bore	O.D.	Width	Width	E	F
FLANGED UNIT	BEARING ONLY	d (in)	D (in)	B (in)	E (in)	E (in)	F (in)
	SUFFIX	+0.005	+0.000	+0.000			
		-0.015	+0.000	+0.000			
		-0.000	-0.005	-0.005			
N6910™	B	0.625	1.6250	0.500	1.000	0.985	0.500
		15.875	41.28	12.70	25.40	24.98	12.70

PRODUCT FEATURES

Brand	NICE
N° Ean13	3616060473363
Shaft diameter	15.875 mm
No. of fasteners	2
Tightening	set screw
Mounting center distance	73.03 mm
Material	TOLE
Weight	150 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE