

Housed bearing 2 bolts N6916-B-NICE - N6916-B-NICE

<https://www.123bearing.eu/bearing-housing/housed-bearing/cast-iron-housed-bearing-2/n6916-b-nice>

6900 Series™ Semi-Ground Radial Bearings, Extended Inner with Flanged Housing **NICE**

- EASY TO USE INCH DIMENSIONS
- MEDIUM LOADS
- MAX SPEED RANGE: 3000 - 3000 RPM
- THROUGH HARDNESS
- RETAINER DESIGN
- NYLON RETAINER STANDARD
- SHOULDER BEADED STANDARD
- EXTENDED INNER RING WITH TWO SET SCREWS
- BEARINGS ARE AVAILABLE WITH OR WITHOUT FLANGES

When Ordering specify whether assembly of bearing only is required.
Bearings are stamped with designation and a "B" for example 6904™B. Housing's no longer carry part numbers.
Tolerance for 6912 and larger is ± 0.020 (-0.005/-0.015)

BEARING		PRINCIPLE DIMENSIONS					
		Bore d	O.D. D	Width B	Width E	E	F
		(in)	(in)	(in)	(in)	(in)	(in)
		(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
FLANGED UNIT	BEARING ONLY	+0.005	+0.000	+0.000			
	SUFFIX	-0.010	+0.000	+0.000			
N6916™	B	1.000	2.0000	0.563	1.063	1.269	0.500
		25.40	50.80	14.29	26.99	32.84	12.70

PRODUCT FEATURES

Brand	NICE
N° Ean13	3616060473387
Shaft diameter	25.4 mm
No. of fasteners	2
Tightening	set screw
Mounting center distance	82.55 mm
Material	TOLE
Weight	150 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE