



Housed bearing accessories 7614-DL-NICE - 7614-DL-NICE

https://www.123bearing.eu/bearing-housing/housed-bearing/accessories/7614-dl-nice

7600 Series™ Heavy Duty Precision Ground Radial Bearings with Extended Inner Ring (con't)

- PRECISION GRINDING ON ALL CONTACT SURFACES
- EASY TO USE DIMENSIONS
- MEDIUM LOADS
- MAX. SPEED RANGE: 5000 - 6000 RPM
- THROUGH HOUSING
- CASE HARDENING
- POLYMER CASE STABILIZER
- PRECISION GRINDING
- IDEALLY APPROPRIATE ANGLES OF CONTACT
- AVAILABLE IN SINGLE RINGS OR OPEN
- EXTENDED INNER RING WITH KEYWAY
- ALL DIMENSIONS UNLESS OTHERWISE SPECIFIED
- RECOMMENDED FOR APPLICATIONS WHERE SPEED, LIFE, AND EFFICIENCY ARE ESSENTIAL FACTORS





BEARING	PRINCIPLE DIMENSIONS					WEIGHT
	BORE		O.D.			
	d (in) (mm)	D (in) (mm)	B (in) (mm)	A (in) (mm)	F (in) (mm)	
7614	+0.0008 +0.000 -0.0000 -0.000	+0.0000 +0.000 -0.0005 -0.013	+0.000 0.000	0.0625 1.58	1.308 33.17	0.136 3.45

PRINCIPLE DIMENSIONS						BASIC LOAD RATINGS		WEIGHT	
H (in) (mm)	J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N 2 set screws	Dynamic C _d (%)	Static C _s (%)		
0.042 1.07	2.158 54.77	1.179 29.95	0.482 12.50	0.261 6.63	1/4-28	0.035 0.89	2070 19217	1550 6098	0.43 0.20

① When ordering please indicate bearing designation and style letters of bearing desired (i.e. DL or DLG)
 ② Tolerance for 7613™ and larger is +0.0000/-0.0005 (+0.000/-0.015)
 ③ Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear
 ④ Weights given are for greased and sealed versions
 All bearing designations listed herein are trademarks of RBC Nice® Bearings.

PRODUCT FEATURES

Brand	NICE
N° Ean13	3616060473455
Inside diameter	22.23 mm
Outside diameter	33.17 mm
Thickness	15.88 mm
Weight	200 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE