Housed bearing accessorie
N6906-NICE - N6906-NICE

https://www.123bearing.eu/bearing-housing/housed-bearing/accessories/n6906-nice



6900 Series™ Semi-Ground Radial Bearings, Extended Inner with Flanged Housing — NICE

- EASY TO USE INCH DIMENSIONS
- MEDIUM LOADS
- MAX SPEED RANGE - 2500 - 3000 RPM
- THROUGH HARDENED
- RETAINER DESIGN
- NYLON RETAINER STANDARD
- DOUBLE SEALED STANDARD
- EXTENDED INNER RING WITH TWO SET SCREWS
- BEARINGS ARE AVAILABLE WITH OR WITHOUT FLANGE

BEARING		PRINCIPLE DIMENSIONS							
FLANGED UNIT	BEARING ONLY	Bore d (in) (mm)	O.D. D (in) (mm)	Width B (in) (mm)	Width C (in) (mm)	E (in) (mm)	F (in) (mm)	G (in) (mm) Bolt Centers	H (in) (mm)
	SUFFIX	+.005 -.000 / +.13 -.00	+.0000 -.0005 / +.00 -.013	+.000 -.005 / +.00 -.13					
N6906™	B	0.375 / 9.53	0.9065 / 23.02	0.313 / 7.94	0.688 / 17.46	0.555 / 14.10	0.375 / 9.53	1.875 / 47.63	2.500 / 63.50

PRINCIPLE DIMENSIONS								BASIC LOAD RATINGS		WEIGHT
J (in) (mm) Overall Width	K (in) (mm)	L (in) (mm)	M (in) (mm)	N (in) (mm)	O 2-Set Screws	P (in) (mm) Hole Dia.	S (in) (mm)	C (lbs) (N)	C_0 (lbs) (N)	W (lbs) (kg)
1.125 / 28.58	0.344 / 8.73	0.344 / 8.73	0.688 / 17.46	0.035 / 0.89	8-32	0.3125 / 7.94	0.000 / 0.00	580 / 2581	300 / 1335	0.07 / 0.03

When Ordering specify whether assembly or bearing only is required. Bearings are stamped with designation and suffix B; for example 6904™B. Housings no longer carry part numbers.

Tolerance for 6912 and larger is +.0000/-.0006 (+000/-.015)

Weights given are for greased and sealed version with flange mount.

PRODUCT FEATURES

Brand	NICE
N° Ean13	3663952564784
Inside diameter	9.53 mm
Outside diameter	23.02 mm
Thickness	7.94 mm
Packaging	1

contact@123bearing.eu
+33 359 36 04 90
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE