

Housed bearing accessories N6916-NICE - N6916-NICE

<https://www.123bearing.eu/bearing-housing/housed-bearing-accessories/n6916-nice>

6900 Series™ Semi-Ground Radial Bearings, Extended Inner with Flanged Housing **NICE**

- EASY TO USE DIMENSIONS
- MEDIUM LOADS
- MAX SPEED RANGE: 2000 - 3000 RPM
- THROUGH HARDENED
- RETAINED DESIGN
- NYLON RETAINER STANDARD
- DOUBLE SEALS STANDARD
- EXTENDED INNER RING WITH TWO SET SCREWS
- BEARINGS ARE AVAILABLE WITH OR WITHOUT FLANGES

BEARING		PRINCIPLE DIMENSIONS							
FLANGED UNIT	BEARING ONLY	Bore d (in) (mm)	O.D. D (in) (mm)	Width B (in) (mm)	Width C (in) (mm)	E (in) (mm)	F (in) (mm)	G (in) (mm)	H (in) (mm)
		+0.005	+0.000	+0.000	+0.000				
		+0.13	+0.00	+0.00	+0.00				
		-0.000	-0.005	-0.000	-0.000				
		-0.00	-0.13	-0.13	-0.13				
N6916	B	1.000	2.000	0.583	1.063	1.293	0.500	3.250	4.125
		25.40	50.80	14.29	26.99	32.84	12.70	82.55	104.78

PRINCIPLE DIMENSIONS								BASIC LOAD RATINGS		WEIGHT
J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N (in) (mm)	O 2-Set Screws	P (in) (mm) Hole Dia.	S (in) (mm)	C (lbs) (N)	C ₀ (lbs) (N)	W (lbs) (kg)
2.250	0.438	0.688	1.125	0.062	10-32	0.4375	0.062	1870	1350	0.33
57.15	11.11	17.48	28.58	1.57		11.11	1.57	8322	6008	0.15

① When Ordering specify whether assembly or bearing only is required. Bearings are stamped with designation and suffix B, for example 6904™B. Housings no longer carry part numbers.
 ② Tolerance for 6912 and larger is +.0000/-0.0006 (+000/-016) ③ Weights given are for greased and sealed version with flange mount.

PRODUCT FEATURES

Brand	NICE
N° Ean13	3663952564814
Inside diameter	25.4 mm
Outside diameter	50.8 mm
Thickness	14.29 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE