

## GE Rod end GE08-ES-2RS-DUNLOP - GE08-ES-2RS-DUNLOP

<https://www.123bearing.eu/bearing-housing/rod-end/ge/ge08-es-2rs-dunlop>

SPHERICAL BEARINGS **DUNLOP**

**GE ES SERIES**



**Description:**  
GE ES-Series is our 2-piece fractured outer ring metric range of spherical plain bearings used in non rotational applications. Ball and race riding surfaces are treated with MoS2 for increased lubricity on wear surface. A lubrication groove is provided on the raceway for applications requiring re-lubrication after installation.

**Material Specifications:**  
Outer ring: Bearing steel 100Cr6, case hardened and manganese phosphated, treated with MoS2. Ball: Bearing steel 100Cr6, case hardened and manganese phosphated. Seals: Polyurethane.

**Features:**  
Metric bore sizes  
Low cost  
Maintenance required  
Up to 140mm bore sizes available

**Possible Applications:**  
Light to heavy industrial mechanical applications  
Construction equipment  
Agricultural equipment  
hydraulic applications

**Temperature Range:**  
-24°C to +121°C

**Specifications:**  
ELV & RoHS compliant

Outer Ring: Bearing Steel 100Cr6, Case Hardened and Manganese Phosphate, wear faces treated with MoS2. Ball: Bearing Steel 100Cr6, Case Hardened and Manganese Phosphate. Seals: Polyurethane.

Part No. Unsealed	Part No. Sealed	Bore Size	W	H	D	Static Load Rating (Newtons) Radial
	GE08ES-2RS	8	8	5	16	27,000

### PRODUCT FEATURES

Brand	DUNLOP
N° Ean13	3616060557421
Inside diameter	8 mm
Inside diameter	0.315" inch
Outside diameter	16 mm
Outside diameter	0.63" inch
Thickness	8 mm
Thickness	0.315" inch
Type	GE
Lubrication	with
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE