

GE Rod end GEZ014-ES-2RS-DUNLOP - GEZ014-ES-2RS-DUNLOP

<https://www.123bearing.eu/bearing-housing/rod-end/ge/gez014-es-2rs-dunlop>

SPHERICAL BEARINGS **DUNLOP**

GEZ ES SERIES



Description:
GEZ-ES-Series is our 2-piece fractured outer ring metric range of spherical plain bearings used in non rotational applications. Ball and race sliding surfaces are treated with MoS2 for increased lubricity on wear surface. A lubrication groove is provided on the raceway for applications requiring re-lubrication after installation.

Material Specifications:
Outer ring: Bearing steel 100Cr6, case hardened and manganese phosphated, treated with MoS2. Ball: Bearing steel 100Cr6, case hardened and manganese phosphated. Seats: Polyurethane.

Features:
Metric bore sizes
Low cost
Maintenance required
Up to 140mm bore sizes available

Possible Applications:
Light to heavy industrial/mechanical applications
Construction equipment
Agricultural equipment
Hydraulic applications

Temperature Range:
-34°C to +121°C

Specification:
ELV & RoHS compliant

Outer Ring: Bearing Steel 100Cr6, Case Hardened and Manganese Phosphate, wear faces treated with MoS2. **Balls:** Bearing Steel 100Cr6, Case Hardened and Manganese Phosphate. **Seats:** Polyurethane

| Part No. Unsealed | Part No. Sealed | Bore Size | W | H | D | Static Load Rating (Newtons) Radial |
|-------------------|-----------------|-----------|--------|--------|--------|-------------------------------------|
| | GEZ014ES-2RS | 7/8 | 19.431 | 16.662 | 36.513 | 127,000 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | DUNLOP |
| N° Ean13 | 5059161262340 |
| Inside diameter | 22.22 mm |
| Inside diameter | 0.875" inch |
| Outside diameter | 36.51 mm |
| Outside diameter | 1 7/16" inch |
| Thickness | 16.66 mm |
| Thickness | 0.656" inch |
| Type | GE |
| Lubrication | with |
| Packaging | 1 |

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE