

GE Rod end GE212-ES-DUNLOP - GE212-ES-DUNLOP

<https://www.123bearing.eu/bearing-housing/rod-end/ge/ge212-es-dunlop>

SPHERICAL BEARINGS




GE ES SERIES

Description:
GE2-ES-Series is our 2-piece fractured outer ring metric range of spherical plain bearings used in non rotational applications. Ball and race sliding surfaces are treated with MoS₂ for increased lubricity on wear surface. A lubrication groove is provided on the raceway for applications requiring re-lubrication after installation.

Material Specifications:
Outer ring: Bearing steel 100Cr6, case hardened and manganese phosphated, treated with MoS₂. Ball: Bearing steel 100Cr6, case hardened and manganese phosphated. Seals: Polyurethane.

Features:
Metric bore sizes
Low cost
Maintenance required
Up to 140mm bore sizes available

Possible Applications:
Light to heavy industrial/mechanical applications
Construction equipment
Agricultural equipment
Hydraulic applications

Temperature Range:
-34°C to +121°C

Specifications:
ELV & RoHS compliant

Outer Ring: Bearing Steel 100Cr6, Case Hardened and Manganese Phosphate, wear faces treated with MoS₂.

Ball: Bearing Steel 100Cr6, Case Hardened and Manganese Phosphate

Seals: Polyurethane

Part No. Unscaled	Part No. Scaled	Bore Size	W	H	D	Static Load Rating (Newtons) Radial
GE212ES		2-3/4	41.112	52.375	111.125	1,250,000

PRODUCT FEATURES

Brand	DUNLOP
N° Ean13	3616060558305
Inside diameter	19.5 mm
Inside diameter	0.768" inch
Outside diameter	61.11 mm
Outside diameter	2.406" inch
Thickness	52.37 mm
Thickness	2.062" inch
Type	GE
Lubrication	with
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE