

Drawn cup roller bearing BA186-Z-IKO - BA186-Z-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/drawn-cup/ba186-z-iko>



Boundary dimensions mm[inch]			Standard mounting dimensions mm				Basic dynamic load rating	Basic static load rating	Allowable rotational speed ⁽¹⁾	Assembled inner ring
<i>F_w</i>	<i>D</i>	<i>C</i>	<i>t₂</i>	<i>H₁</i>	<i>J₁</i>	<i>C</i>	<i>C₀</i>	rpm		
	Max.	Max.	Max.	Min.	Max.	Min.	N	N	rpm	
28.575 (1.124)	34.925 (1.375)	9.52 (0.375)	2.6				6330	8910	13000	...

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060601247
Inside diameter	28.575 mm
Inside diameter	1 1/8" inch
Outside diameter	34.925 mm
Outside diameter	1 3/8" inch
Thickness	9.52 mm
Thickness	0.375" inch
Limiting speed	13000 rpm
Dynamic load	6.33 kN
Static load	8.91 kN
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE