

## Drawn cup roller bearing BA2620-Z-IKO - BA2620-Z-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/drawn-cup/ba2620-z-iko>



Boundary dimensions mm[inch]			Standard mounting dimensions mm				Basic dynamic	Basic static	Allowable	Assembled
$F_w$	D	C	Shaft dia.	Housing bore dia.		load rating	load rating	rotational	inner ring	
			d	H	J	C	CP	speed(r)		
			Max.	Max.	Min.	Max.	Min.	N	N	
								rpm		
41.275 (1 5/8)	50.8 (2)	31.75 (1.250)	2.8					41400	82100	8000

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060601506
Inside diameter	41.275 mm
Inside diameter	1 5/8" inch
Outside diameter	50.8 mm
Outside diameter	2" inch
Thickness	31.75 mm
Thickness	1 1/4" inch
Limiting speed	8000 rpm
Dynamic load	41.4 kN
Static load	82.1 kN
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE