


Tapered roller bearing JP6049-JP6010-TIMKEN - JP6049-JP6010-TIMKEN

https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/jp6049-jp6010-timken

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS



| Bearing Dimensions | | | Load Ratings | | | | | | | Part Number | |
|--------------------|---------|---------|---------------------------------------|-------------------------|---------------------------------------|--------------------------------------|-----------------------|-------------------------|-----------------------|-------------|--------|
| Bore d | O.D. D | Width B | Dynamic ⁽¹⁾ C ₁ | Factor ⁽²⁾ e | Dynamic ⁽¹⁾ C ₂ | Factor ⁽²⁾ e ₂ | Static C ₀ | Factor ⁽²⁾ K | Static C ₀ | Inner | Outer |
| mm | mm | mm | N | | N | | N | | N | | |
| 60.000 | 105.000 | 21.000 | 8250 | 0.24 | 21400 | 1.24 | 101000 | 1.24 | 101000 | JP6049 | JP6010 |
| 2.2822 | 3.9370 | 0.8268 | 18500 | | 4810 | | 22800 | | 22800 | | |

| Bearing Dimensions | | | | | | | | | | Geometry Factors | | | Bearing Weight | |
|--------------------|--------|---------|------|-------|------|---------|------|------|------|------------------|----------------|----------------|----------------|------|
| Width B | | ER. Cr. | | Shaft | | Housing | | Cage | | G ₁ | G ₂ | C ₃ | | |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | | | | kg | |
| 20.000 | 15.500 | 1.3 | 2.8 | 66.0 | 65.8 | 2.8 | 35.5 | 31.8 | 1.4 | 2.8 | 35.5 | 22.5 | 0.8020 | 0.88 |
| 0.7874 | 0.6102 | 0.05 | 0.08 | 2.60 | 2.72 | 0.08 | 3.76 | 3.58 | 0.05 | 0.12 | | | 1.31 | |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | TIMKEN |
| N° Ean13 | 3663952110868 |
| Inside diameter | 60 mm |
| Outside diameter | 105 mm |
| Weight | 590 g |
| Packaging | 1 |
| Standard | No standard |

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE