

## Adhesive

### EA-109-320ML-LOCTITE - EA-109-320ML-LOCTITE

<https://www.123bearing.eu/lubricant-adhesive/adhesive/adhesive/ea-109-320ml-loctite>

TITRE	Epoxy
DESCRIPTION	Monocomposant, viscosité moyenne, à chaud
NOM	LOCTITE EA 109
CONDITIONNEMENT	Ca 320 ml
DANGEROUS GOODS	Yes
COMMENTAIRE	
APPROBATION	

#### Description

LOCTITE® EA 109 is a cream, 1-part, high temperature, epoxy adhesive designed to provide maximum resistance to impact, shear, cleavage and tensile loads. The best results are achieved by heat curing. It is electrically non-conductive. Industry applications include automotive, manufacturing, magnet bonding, filter gaskets. Service temperature range: -40 to +180°C.

#### Avantages

Will bond to a wide variety of surfaces, including oily steel, and performance is usually limited by the strength of the substrates themselves. Durability, chemical resistance and high temperature performance are extremely good. Can replace traditional fixing techniques to give enhanced appearance and greater design flexibility.

#### Caractéristiques

Cream, 1-part, high temperature, epoxy adhesive designed to provide maximum resistance to impact, shear, cleavage and tensile loads.

## PRODUCT FEATURES

Brand	LOCTITE
N° Ean13	5010266009186
Type	COLLAGE RIGIDE EPOXY ACRYLIQUE
Weight	585 g
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE