


Housed bearing 2 bolts P2BC-35M-CPSS-DFH-SKF - P2BC-35M-CPSS-DFH-SKF

<https://www.123bearing.eu/bearing-housing/housed-bearing/cast-iron-housed-bearing-2/p2bc-35m-cpss-dfh-skf>

Données de calcul		
Charge dynamique de base	C	21.8 kN
Charge statique de base	C ₀	15.3 kN
Limite de fatigue	F _r	0.655 kN
Conformité avec standard	Not standardized	
Matérial	Composite for the SKF Food Line	
Solution d'étanchéité	Gutter seals	
Dimensions		
	d	35 mm
	A	40 mm
	A ₁	40 mm
	A ₂	68.6 mm
	B	34.9 mm
	B ₁	6 mm
	B ₂	63.8 mm
	H ₁	47.6 mm
	H ₂	26 mm
	J	127 mm
	J _{max}	130 mm
	J _{min}	124 mm
	L	168 mm
	N ₁	17 mm
N ₂	14 mm	
r _s	25.4 mm	
Photo de montage		
G	12 mm	
G ₁	0.5 in	
Calculation data		
Limiting speed	300	rpm
with shaft tolerance H6		

PRODUCT FEATURES

Brand	SKF
N° Ean13	7316577856005
Shaft diameter	35 mm
No. of fasteners	2
Tightening	Eccentric locking ring
Mounting center distance	127 mm
Material	FOOD-GRADE POLYPROPYLENE
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE