


Housed bearing 2 bolts P2BC-40M-CPSS-DFH-SKF - P2BC-40M-CPSS-DFH-SKF

<https://www.123bearing.eu/bearing-housing/housed-bearing/cast-iron-housed-bearing-2/p2bc-40m-cpss-dfh-skf>

Données de calcul			
Charge dynamique de base	C	24.7	kN
Charge statique de base	C ₀	19	kN
Limite de fatigue	P ₀	0.8	kN
Compliance with standard		Not standardized	
Matériau		Compatible for the SKF Food Line	
Sealing solution		Gutter seals	
Dimensions			
			
d	40	mm	
A	44	mm	
A ₁	44	mm	
A ₂	79.9	mm	
B	40.7	mm	
B ₁	10	mm	
B ₂	38.3	mm	
H ₁	49.2	mm	
H ₂	20	mm	
J	137	mm	
J ₁	max. 140	mm	
J ₂	min. 134	mm	
L	179	mm	
N	17	mm	
N ₁	14	mm	
N ₂	30.2	mm	
Plots de centrage			
G	12	mm	
G ₁	6.6	in	
Calculation data			
Limiting speed		900	min
with shaft tolerance H8			

PRODUCT FEATURES

Brand	SKF
N° Ean13	7316577859327
Shaft diameter	40 mm
No. of fasteners	2
Tightening	Eccentric locking ring
Mounting center distance	137 mm
Material	FOOD-GRADE POLYPROPYLENE
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE