

# Tapered roller bearing 33122-JR-JTEKT - 33122-JR-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/33122-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>				
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.						
110	180	56	56	43	389	634	2 000	2 700	33122JR					
Dimension series to ISO 995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>1a</sub> min.	r <sub>1a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
3EE	44.5	122	121	170	155	174	9	13	2	2	0.42	1.43	0.79	5.52

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250126475
Inside diameter	110 mm
Outside diameter	180 mm
Thickness	56 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE