

## Tapered roller bearing 323-32-R-JTEKT - 323-32-R-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/323-32-r-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	C <sub>90</sub>	C <sub>100</sub>	Grease lub.	Oil lub.	
32	75	29.75	28	25	89.6	101	5 600	7 400	323/32R		

  

Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>1</sub> min.	d <sub>2</sub> max.	D <sub>1</sub> max.	D <sub>2</sub> min.	S <sub>1</sub> min.	S <sub>2</sub> min.	r <sub>3</sub> min.	r <sub>4</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
—	19.6	40.5	42	66.5	63	69	3	4.5	1.5	1.5	0.32	1.88	1.04	0.650

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952400792
Inside diameter	32 mm
Outside diameter	75 mm
Thickness	29.75 mm
Weight	649 g
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE