

Tapered roller bearing 32207-1R-JTEKT - 32207-1R-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/32207-1r-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
35	72	24.25	23	19	69.0	86.6	5 700	7 600	32207-1R					
Dimension series to ISO 955 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
—	21.1	43.5	42	63.5	56	68	3	5	1.5	1.5	0.58	1.04	0.57	0.485

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952400822
Inside diameter	35 mm
Outside diameter	72 mm
Thickness	24.25 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE