

## Tapered roller bearing T2EE040-JTEKT - T2EE040-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/t2ee040-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>				
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.						
40	85	33	32.5	28	114	143	4 800	6 400	T2EE040					
Dimension series to ISO95 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>1a</sub> min.	r <sub>1a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
2EE	21.9	52	48	75	70	80	5	5	2	2	0.34	1.74	0.96	0.900

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952404899
Inside diameter	40 mm
Outside diameter	85 mm
Thickness	33 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE