

Tapered roller bearing 32311-C-JTEKT - 32311-C-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/32311-c-jtekt>

Single-row tapered roller bearings
metric series

Koyo



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | | | Limiting speeds (min ⁻¹) | | Bearing No. ¹⁾ | | | | |
|---------------------------------------|--------------------|--------------------------|----------------------|-------------------------|----------------------|----------------------|----------------------|--------------------------------------|----------------------|---------------------------|--------------------|----------------|----------------------|------|
| d | D | T | B | C | C _r | C _{0r} | Grease lub. | Oil lub. | | | | | | |
| 55 | 120 | 45.5 | 43 | 35 | 184 | 247 | 3 400 | 4 600 | 32311C | | | | | |
| Dimension series to ISO995 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) | | | | | | | | Constant e | Axial load factors | | (Refer. 1) Mass (kg) | |
| | | d _{1a} min. | d _{1a} max. | D _{1a} min. | D _{1a} max. | S _{1a} min. | S _{1a} max. | r _{1a} min. | r _{1a} max. | | Y ₁ | Y ₀ | | |
| SFD | 35.9 | 67 | 67 | 108 | 90 | 113 | 4 | 10 | 2 | 2 | 0.55 | 1.10 | 0.60 | 2.45 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3663952405889 |
| Inside diameter | 55 mm |
| Outside diameter | 120 mm |
| Thickness | 45.5 mm |
| Packaging | 1 |

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE