

Tapered roller bearing 33114-JR-JTEKT - 33114-JR-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/33114-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.	
70	120	37	37	29	2	1.5	181	266	3 100	4 200	33114JR

Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
3DE	28.0	80	79	110	104	115	6	8	2	1.5	0.38	1.58	0.87	1.71

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952409061
Inside diameter	70 mm
Outside diameter	120 mm
Thickness	37 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE