

Tapered roller bearing T2ED070-JTEKT - T2ED070-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/t2ed070-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.	
70	130	43	42	35	3	2.5	233	319	3 000	4 000	T2ED070

Dimension series to ISO 995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
2ED	30.2	84	81	118	111	123	1	1	2.5	2	0.33	1.80	0.99	2.48

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250067310
Inside diameter	70 mm
Outside diameter	130 mm
Thickness	43 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE