

Tapered roller bearing 30317-R-JTEKT - 30317-R-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/30317-r-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾			
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.				
85	180	44.5	41	34	305	367	2 200	2 900	30317R					
Dimension series to ISO 955 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
—	35.8	103	107	166	156	167	5	10.5	3	2.5	0.35	1.73	0.95	4.97

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250122286
Inside diameter	85 mm
Outside diameter	180 mm
Thickness	44.5 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE