

Tapered roller bearing 32317-JR-JTEKT - 32317-JR-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/32317-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | | | Limiting speeds (min ⁻¹) | | Bearing No. ¹⁾ | | | | |
|--|--------------------|--------------------------|----------------------|-------------------------|----------------------|----------------------|----------------------|--------------------------------------|----------------------|---------------------------|--------------------|----------------|----------------------|------|
| d | D | T | B | C | C _r | C _{0r} | Grease lub. | Oil lub. | | | | | | |
| 85 | 180 | 63.5 | 60 | 49 | 439 | 587 | 2 200 | 3 000 | 32317JR | | | | | |
| Dimension series to ISO 995 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) | | | | | | | | Constant e | Axial load factors | | (Refer. 1) Mass (kg) | |
| | | d _{1a} min. | d _{1a} max. | D _{1a} min. | D _{1a} max. | S _{1a} min. | S _{1a} max. | r _{1a} min. | r _{1a} max. | | Y ₁ | Y ₀ | | |
| 260 | 43.8 | 103 | 103 | 166 | 150 | 167 | 5 | 14.5 | 3 | 2.5 | 0.35 | 1.74 | 0.96 | 7.42 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 4549250125225 |
| Inside diameter | 85 mm |
| Inside diameter | 3.346" inch |
| Outside diameter | 180 mm |
| Outside diameter | 7.087" inch |
| Thickness | 63.5 mm |
| Thickness | 2 1/2" inch |
| Packaging | 1 |

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE