

## Tapered roller bearing 33219-JR-JTEKT - 33219-JR-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/33219-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>				
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.						
95	170	58	58	44	3	2.5	374	582	2 200	2 900	<b>33219JR</b>			
Dimension series to ISO 955 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	d <sub>2a</sub> min.	d <sub>2a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>1a</sub> min.	r <sub>1a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
3FE	42.8	109	107	158	144	163	9	14	2.5	2	0.41	1.47	0.81	5.66

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952409788
Inside diameter	95 mm
Outside diameter	170 mm
Thickness	58 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE