

# Tapered roller bearing 30319-JR-JTEKT - 30319-JR-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/30319-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



| Boundary dimensions (mm)             |                  |                          |                     | Basic load ratings (kN) |                     |                      |                     | Limiting speeds (min <sup>-1</sup> ) |                     | Bearing No. <sup>1)</sup> |                    |                |                    |      |
|--------------------------------------|------------------|--------------------------|---------------------|-------------------------|---------------------|----------------------|---------------------|--------------------------------------|---------------------|---------------------------|--------------------|----------------|--------------------|------|
| d                                    | D                | T                        | B                   | C                       | C <sub>r</sub>      | C <sub>0r</sub>      | Grease lub.         | Oil lub.                             |                     |                           |                    |                |                    |      |
| 95                                   | 200              | 49.5                     | 45                  | 38                      | 372                 | 455                  | 2 000               | 2 600                                | 30319JR             |                           |                    |                |                    |      |
| Dimension series to ISO 995 (Refer.) | Load center (mm) | Mounting dimensions (mm) |                     |                         |                     |                      |                     |                                      |                     | Constant e                | Axial load factors |                | (Refer.) Mass (kg) |      |
|                                      |                  | d <sub>1a</sub> min.     | d <sub>2</sub> max. | D <sub>1a</sub> max.    | D <sub>2</sub> min. | S <sub>1a</sub> min. | S <sub>2</sub> min. | r <sub>3a</sub> min.                 | r <sub>4</sub> max. |                           | Y <sub>1</sub>     | Y <sub>0</sub> |                    |      |
| 20B                                  | 40.8             | 113                      | 118                 | 186                     | 172                 | 186                  | 5                   | 11.5                                 | 3                   | 2.5                       | 0.35               | 1.74           | 0.96               | 6.96 |

## PRODUCT FEATURES

|                  |               |
|------------------|---------------|
| Brand            | JTEKT         |
| N° Ean13         | 3663952409818 |
| Inside diameter  | 95 mm         |
| Outside diameter | 200 mm        |
| Thickness        | 49.5 mm       |
| Packaging        | 1             |

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE