

# Tapered roller bearing T4CB100-JTEKT - T4CB100-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/t4cb100-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>			
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	C <sub>90</sub>	C <sub>100</sub>	Grease lub.	Oil lub.				
100	145	24	22.5	17.5	3	3	116	167	2 400	3 200	T4CB100			
Dimension series to ISO95 (Refer. I)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. I) Mass (kg)	
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>1a</sub> min.	r <sub>1a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
4CB	29.9	112	109	133	132	140	4	6.5	2.5	2.5	0.47	1.27	0.70	1.12

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952410500
Inside diameter	100 mm
Outside diameter	145 mm
Thickness	24 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE