

Tapered roller bearing 33120-JR-JTEKT - 33120-JR-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/33120-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾			
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.				
100	165	52	52	40	325	523			2 200	3 000	33120JR			
Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	d _{2a} min.	d _{2a} max.	S _{1a} min.	S _{1a} max.	r _{3a} min.	r _{3a} max.		Y ₁	Y ₀		
3EE	40.1	112	111	155	142	159	8	12	2	2	0.41	1.48	0.81	4.29

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250126468
Inside diameter	100 mm
Outside diameter	165 mm
Thickness	52 mm
Packaging	1
Standard	No standard

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE