

Tapered roller bearing 30320-JTEKT - 30320-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/30320-jtekt>

Single-row tapered roller bearings
metric series

Koyo



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | | | Limiting speeds (min ⁻¹) | | Bearing No. ¹⁾ | | | | |
|--|--------------------|--------------------------|----------------------|-------------------------|----------------------|----------------------|----------------------|--------------------------------------|----------------------|---------------------------|--------------------|----------------|----------------------|------|
| d | D | T | B | C | C _r | C _{0r} | Grease lub. | Oil lub. | | | | | | |
| 100 | 215 | 51.5 | 47 | 39 | 344 | 400 | 1 800 | 2 400 | 30320 | | | | | |
| Dimension series to ISO 355 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) | | | | | | | | Constant e | Axial load factors | | (Refer. 1) Mass (kg) | |
| | | d _{1a} min. | d _{1a} max. | D _{1a} min. | D _{1a} max. | S _{1a} min. | S _{1a} max. | r _{1a} min. | r _{1a} max. | | Y ₁ | Y ₀ | | |
| — | 41.4 | 118 | 127 | 201 | 184 | 200 | 6 | 12.5 | 3 | 2.5 | 0.35 | 1.73 | 0.95 | 7.76 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 4549250122408 |
| Inside diameter | 100 mm |
| Outside diameter | 215 mm |
| Thickness | 51.5 mm |
| Packaging | 1 |

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE