

Tapered roller bearing 31320-JR-JTEKT - 31320-JR-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/31320-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.	
100	215	56.5	51	35	373	459	1 500	2 200			31320JR

Dimension series to ISO 355 (Refer.)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer.) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
7GB	67.7	118	120	201	183	202	6	17.5	3	2.5	0.83	0.73	0.40	8.72

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250122828
Inside diameter	100 mm
Inside diameter	3.937" inch
Outside diameter	215 mm
Outside diameter	8.465" inch
Thickness	56.5 mm
Thickness	2.224" inch
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE