

## Tapered roller bearing 32921-JR-JTEKT - 32921-JR-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/32921-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	C <sub>90</sub>	C <sub>100</sub>	Grease lub.	Oil lub.	
105	145	25	25	20	128	224	2 400	3 100	32921JR		

  

Dimension series to ISO 355 (Refer.)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer.) Mass (kg)	
		d <sub>1</sub> min.	d <sub>2</sub> max.	D <sub>1</sub> max.	D <sub>2</sub> min.	S <sub>1</sub> min.	S <sub>2</sub> min.	r <sub>1</sub> max.	r <sub>2</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
20C	25.1	113.5	113	136.5	133	140	5	5	1.5	1.5	0.34	1.75	0.96	1.23

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250125621
Inside diameter	105 mm
Inside diameter	4.134" inch
Outside diameter	145 mm
Outside diameter	5.709" inch
Thickness	25 mm
Thickness	0.984" inch
Weight	1230 g
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE