

Tapered roller bearing 33221-JR-JTEKT - 33221-JR-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/33221-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾
d	D	T	B	C	C _r	C _{0r}	C _{0r}	Grease lub.	Oil lub.		
105	190	68	68	52	497	790		2 000	2 600	33221JR	

Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
3FE	48.8	119	117	178	159	182	10	16	2.5	2	0.40	1.49	0.82	8.43

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250241437
Inside diameter	105 mm
Outside diameter	190 mm
Thickness	68 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE