

Tapered roller bearing 32922-JR-JTEKT - 32922-JR-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/32922-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
110	150	25	25	20	129	231	2 300	3 000	32922JR					
Dimension series to ISO 995 (Refer.)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer.) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
20C	26.3	119	118	141	138	145	5	5	1.5	1.5	0.96	1.69	0.93	1.28

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250125645
Inside diameter	110 mm
Inside diameter	4.331" inch
Outside diameter	150 mm
Outside diameter	5.906" inch
Thickness	25 mm
Thickness	0.984" inch
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE