

Tapered roller bearing 30322-JTEKT - 30322-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/30322-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
110	240	54.5	50	42	407	475	1 600	2 100	30322					
Dimension series to ISO 995 (Refer.)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer.) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
—	44.8	128	141	226	206	222	8	12.5	3	2.5	0.35	1.73	0.95	10.4

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250122453
Inside diameter	110 mm
Inside diameter	4.331" inch
Outside diameter	240 mm
Outside diameter	9.449" inch
Thickness	54.5 mm
Thickness	2.146" inch
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE